

Vended **Galaxy™ 500** Hardmount Washer-Extractors



Today's vended laundry customers want easy-to-use machines that produce great wash results and get them in and out fast. Huebsch® hardmount washer-extractors deliver in all those areas to ensure your laundromat is as profitable as it is efficient. In addition, their legendary durability provides peace of mind that the machines will be consistent performers for your business for years to come.

Strength

Our computer-optimized, heavy-duty frame is lighter, lasts longer, balances loads more efficiently, and reduces sound and vibration levels. Huebsch washer-extractors also boast two triple-lip seals and an excluder-face seal for seven layers of bearing protection.

Power

Proprietary inverter-drive technology provides smooth, reliable power, saving you 33% on electricity while maximizing cleaning power. Our inverter also exerts 200 G-Force extraction to remove more moisture from loads and reduce drying time.

Performance

Available in a variety of capacities, including 20 lb, 30 lb, 40 lb, 60 lb, 80 lb and 100 lb capacities, Huebsch cabinet hardmount washer-extractors also offer a variety of control options to match your operation's unique requirements.



Galaxy™ 500

With a 200 G-Force option that customers love and eight cycle options, Galaxy 500 delivers the flexibility to tailor washes, while multi-level vend opens up increased profit potential for owners. Best of all, the control is simple to operate – making it easy for every customer to get the wash they want. In addition, quick programming and 30 water levels enable owners to adapt to changes in their market, while access to audit data keeps them apprised of activity in the operation.

Vended **Galaxy™ 500 Washer-Extractors** Specifications

Models			HCT020	HCT030	HCT040	HCT060	HCT080	HCT100
Control Options			Galaxy™ 500	Galaxy™ 500	Galaxy™ 500	Galaxy™ 500	Galaxy™ 500	Galaxy™ 500
Capacity – lb (kg)			20 (9)	30 (13.6)	40 (18)	60 (27)	80 (36)	100 (45)
Overall Width – in (mm)			26 (660)	29 (737)	30.6 (777)	34.1 (866)	41.5 (1054)	41.5 (1054)
*Overall Depth – in (mm)			30.9 (785)	35.3 (897)	42.3 (1074)	44.7 (1135)	47.1 (1196)	51.1 (1298)
Overall Height – in (mm)			43 (1092)	45 (1143)	47.2 (1199)	49.9 (1267)	57.2 (1453)	57.2 (1453)
Cylinder Diameter – in (mm)			21 (533)	24 (610)	26.3 (668)	30 (762)	36 (914)	36 (914)
Cylinder Depth – in (mm)			13.8 (351)	16 (406)	20.3 (516)	22 (559)	21.9 (556)	25.9 (658)
Cylinder Volume – cu ft (liters)			2.8 (79)	4.2 (119)	6.3 (178)	9 (225)	12.9 (365)	15.2 (430)
Door Opening Size – in (mm)			11.6 (295)	14.3 (363)	16.3 (414)	16.3 (414)	18.5 (470)	18.5 (470)
Door Bottom to Floor – in (mm)			14.4 (366)	14 (356)	14.6 (371)	14.9 (378)	17.9 (455)	17.9 (455)
Water Inlet Connection – in (mm)			2 x 0.75 (19)	2 x 0.75 (19)	2 x 0.75 (19)	4 x 0.75 (19)	4 x 0.75 (19)	4 x 0.75 (19)
Drain Diameter – in (mm)			1 x 3 (76)	1 x 3 (76)	1 x 3 (76)	1 x 3 (76)	1 x 3 (76)	1 x 3 (76)
Drain Height to Floor – in (mm)			3.9 (99)	4.3 (109)	4.5 (114)	4.9 (124)	5.1 (130)	5.1 (130)
Motor Power Consumption – HP(kW)			1 (0.75)	1 (0.75)	2 (1.5)	3 (2.2)	5 (3.7)	5 (3.7)
Total # of Speeds			6, 9	6, 9	6, 9	6, 9	6, 9	6, 9
**Cylinder Speeds – RPM (G-Force)			Gentle	37 (0.4)	34 (0.4)	33 (0.4)	31 (0.4)	28 (0.4)
			Wash	51 (0.8)	48 (0.8)	46 (0.8)	43 (0.8)	39 (0.8)
			Distribution	92 (2.5)	86 (2.5)	82 (2.5)	77 (2.5)	70 (2.5)
			Very Low	301 (27)	282 (27)	269 (27)	252 (27)	230 (27)
			Low	518 (80)	485 (80)	464 (80)	434 (80)	396 (80)
			Medium	579 (100)	542 (100)	518 (100)	485 (100)	443 (100)
			High	648 (125)	606 (125)	579 (125)	542 (125)	495 (125)
			Very High	710 (150)	664 (150)	635 (150)	594 (150)	542 (150)
			Ultra High	819 (200)	766 (200)	733 (200)	686 (200)	626 (200)
*** Voltage/ Circuit Breaker - FLA	B	120/60/1	15-9	15-12	20-15	N/A	N/A	N/A
	X	200-240/50-60/1/3	15-4 (1 Ph) 15-3 (3 Ph)	15-7 (1 Ph) 15-4 (3 Ph)	15-7 (1 Ph) 15-4 (3 Ph)	15-11 (1 Ph) 15-7 (3 Ph)	20-15 (1 Ph) 15-9 (3 Ph)	20-16 (1 Ph) 15-10 (3 Ph)
	Y	200-240/60/1/3 (Pump Drain Only)	15-4 (1 Ph)	15-7 (1 Ph) 15-4 (3 Ph)	15-7 (1 Ph) 15-4 (3 Ph)	N/A	N/A	N/A
Shipping Dimensions Approx. – in (mm)			Width	28 (711)	31.5 (800)	32.5 (826)	37.5 (953)	44 (1118)
			Depth	33.8 (859)	38.3 (973)	43.5 (1105)	46.9 (1191)	54.5 (1384)
			Height	49.4 (1255)	51.3 (1303)	53.6 (1361)	56.3 (1430)	59.6 (1514)
Net Weight – lb (kg)			340 (154)	440 (200)	540 (245)	680 (308)	1250 (567)	1280 (581)
Shipping Weight – lb (kg)			380 (172)	480 (218)	580 (263)	720 (327)	1300 (590)	1330 (603)
Slat Crate Shipping Weight – lb (kg)			460 (209)	580 (263)	680 (308)	840 (381)	1430 (649)	1460 (662)
***Agency Approvals			cULus	cULus	cULus	cULus	cULus	cULus

*Overall depth includes vacuum breaker to door handle.

**High, Very High, and Ultra High Spin Speeds are available on select Galaxy 500 models only.

***Circuit breaker and amp draw data shown are for models without electric heat. Consult factory for other configurations. Manufacturer strongly recommends using a circuit breaker instead of fuses. Use 3-pole circuit breakers for 3-phase machines.

***Agency approvals may vary depending on configuration. Consult factory for details. Steam connection requires 1/2" N.P.T.

For the most accurate information, the installation guide should be used for all design and construction purposes. Due to continuous product improvements, design and specifications subject to change without notice. The quality management system of Alliance Laundry Systems has been registered to ISO 9001.